

Integrated Approach for Before Landslide Monitoring and Prevention Using Sensor Technology and Drone Mapping

Vikash Kumar¹✉, Dr. Sushil Kumar*²✉

^{1,2}Amity Institute of Information Technology, Amity University, Patna, INDIA

Corresponding Author: skumar@ptn.amity.edu



This is an open-access article distributed under the terms of the [Creative Commons Attribution 4.0 International License](https://creativecommons.org/licenses/by/4.0/), which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.

Abstract: The usage of drone mapping and sensor era, together with an included technique for tracking and stopping landslides, gives a complete way to lower the risks related to landslides. This technique allows determine affected regions effectively, hit upon possible dangers early and maintain music of landslide-prone areas in real time via combining advanced sensors with drone-based mapping. This revolutionary approach helps hold groups secure and supports healing efforts after disasters, as well as allows brief preventive moves. By using drone mapping and sensor technology, officials can minimize the effects of landslides in mountainous areas by acting based on real-time data.

Keywords: Sensor and drone technology, Landslide tracking and prevention, Drone mapping, Real-time monitoring, Hazard assessment, post-disaster management, Prevention measures, Soil moisture, Surveillance.

Introduction

In steep areas, landslides can cause major dangers to both buildings and people. Many times, damage and loss of life happen because traditional methods for monitoring and preventing landslides are only reactive, not proactive. To make landslide monitoring and prevention more effective, this article proposes a combined approach that uses sensor technology and drone mapping.

- Suggests a combined system for monitoring landslides that uses both ground sensors and drones to better assess risks.
- Gives a manner to monitor landslides in real time and warn human beings early by means of combining statistics from moisture sensors, tilt sensors, vibration sensors, and drones.
- Affords an unmarried technique that facilitates expect landslides earlier than they occur and investigate damage after an occasion occurs.



- Make use of mathematical models and risk elements to research soil balance, slope movement, and ground vibrations to decide which landslides are probably to manifest.
- This suggests how this technique can be used correctly by disaster control teams in areas wherein landslides are common and the land is hilly.

Literature Review

Previous Art has proven that spotting early signs and symptoms and closely tracking areas can assist prevent landslides. Research has discovered that using advanced sensors and drones could make responses quicker and threat checks greater accurately. However, there's nonetheless a need for a full system that makes use of that technology for each getting ready for and responding to landslides after they take place. Although there has been a whole lot of development in the use of sensor technology and drone-based totally mapping to monitor landslides, most studies focus on these methods one after the other and most effectively cover certain elements of landslide management. a few research look at the usage of ground sensors for early warnings, while others use drones to analyse the land. However, none provides a single machine that combines statistics from diverse sensors with real-time aerial monitoring. Also, much research is most effective to observe predicting landslides before they occur or assessing harm after they manifest, without creating a gadget that manages both levels constantly. Because of this, there's a clean want for research that develops an included, real-time framework that mixes sensor information, drone mapping, and facts fusion strategies for complete landslide tracking, early warning, prevention, and recuperation efforts.

This paper fills that hole by imparting a comprehensive approach that allows making higher choices and decreases dangers in areas where landslides are common.

Comprehensive Framework for Pre-catastrophe and Publish-Disaster Management the Use of Sensor technology and Drone Mapping

Landslides pose a severe hazard to the surroundings, infrastructure, and people's lives. To decrease these risks, it's miles important to have right monitoring and prevention techniques in place. This look presents a detailed method for coping with landslide-inclined areas each earlier

than and after an occasion, the use of superior gear like sensors and drone-primarily based mapping [1]. The studies soil moisture which is collect the data from unstable areas high risk areas before landslides happen and stable areas without any landslide. Clearly this information helps in comparing and analysis the risk levels in **Figure 1**.




Figure 1: Architecture Description or Sensor Technology

Table1: Soil Moisture Data Collection Strategy

Location Category	Purpose
Post-Landslide Area	Understand failure conditions and moisture thresholds
Pre-Landslide High-Risk Area	Detect early warning signs and rising instability
Stable Non-Landslide Area	Establish baseline moisture reference

Pre-Disaster Management

Sensor Technology

- **Sensors for Soil Moisture:** These instruments monitor the moisture level of the soil which is essential to forecast landslides. High levels of moisture could indicate a high-level risk of landslides.
- **Telemeters:** They detect before alerts for chances landslides and measure the location as a slope changes.
- **Geophones:** These sensors monitor ground vibration which could suggest a coming landslide [2].



Unmanned Aerial Systems

Topographical Mapping: Drone uses LiDAR and photogrammetric cameras to create detailed and spot regions that could pose risks [3].

Vegetation Analysis: Soil strength is impacted by vegetation cover and may be looked at with drones.

Infrared imaging: This technique helps determine the moisture level of the soil and structure.

Combination and Evaluation

Data Fusion: Combining data into different types of sensors and drone scan given details about danger.

Real-Time Monitoring: Authorities are able to monitor conditions and predict possible landslides by always collecting data and analysis data [4].

Immediate Response

Damage Assessment: Drones always provide excellent photos, video and data for damage evaluation and quickly check and impacted region.

Search and Rescue: Drones tools with infrared photo sensor help to the survival hunt [5].

Recovery and Rehabilitative Care

Infrastructure Assessment: Checking if the use of full maps helps well-maintained roads, bridges and structures.

Environmental Impact Assessment: Knowing the nature of environmental harm is key to figuring out how to fix it.

Extended Observation

Monitoring of Rehabilitation: If restore areas are under surveillance with sensors and drones keeping identified to assure security and stability [6].

Preventive Measures: Continuous data collection to help create and carry out more effective methods to minimize risk in the future.

Technologies Used

A detailed Survey of Sensor Technology for Landslide Monitoring and control

Sensors for Soil Moisture

Idea: The moisture level of the soil is measured using soil moisture sensors and this data is essential for landslide warning. Slope collapse is more likely when soil moisture content is high since it reduces the soil's shear strength [7].

Equation: The dielectric constant of the soil, which is influenced by its moisture content, is commonly used to compute the volumetric water content (θ). The association provided by Topp et al. (1980) is a common one.

$$\theta = a_0 + a_1\varepsilon + a_2\varepsilon^2 + a_3\varepsilon^3$$

Where:

- θ = Volumetric water content
- ε = Dielectric constant of the soil
- a_0, a_1, a_2, a_3 = Empirical coefficients determined experimentally

Table 2: Landslide Risk and Soil Moisture Levels

Moisture Level (%)	Landslide Risk
0-10	Low
10-20	Moderate
20-30	High
>30	Very High

Tilt meters

Idea: By measuring the angle at which a slope moves, tilt meters can identify changes in the slope's inclination and provide early warning signs of impending landslides.

Equation: The tilt angle (α) can be calculated using the arc tangent function of the ratio of vertical displacement (Δh) to the horizontal distance (L):

$$\alpha = \arctan\left(\frac{\Delta h}{L}\right)$$

1) 4.1.3 Vibration Analysis Model (Geophone)

Idea: Ground vibrations, which can signal seismic activity or ground movement preceding landslides, are picked up using geophones.

Equation: The ground vibrations' frequency (f) and velocity (V) are linked to the displacement (D) that a geophone detects:

$$D = \frac{V}{2\pi f}$$

Table 3: Amplitude of Vibration and Risk of Landslides

Vibration Amplitude (mm)	Landslide Risk
0-1	Low
1-5	Moderate
5-10	High
10	Very High

Soil Moisture Sensor Calibration Data

Following is Table 2,3 showing a mapping between sensor data and matching moisture levels. It probably acts as a calibration table for a moisture content sensor or device, such as humidity or soil moisture sensor.




Figure 2: Moisture Levels and Sensor Reading

Moisture Levels and Sensor Readings

The relationship between moisture levels and sensor readings is depicted in the line chart you provided by Figure 2. The sensor values are shown on the x-axis, while the related moisture levels are shown on the x-axis.

- **Negative connection:** There is a negative connection between the two variables, as moisture levels fall as sensor readings rise.
- **Zero Crossing:** At a sensor reading of 700, the moisture level crosses zero. This raises the possibility of a threshold at which the moisture content changes from positive to negative.
- **Linear Trend:** Throughout the range of sensor readings, there appears to be a steady rate of change in the relationship between the variables.



Sensor Reading: This is a representation of the sensor's raw numerical value. Depending on the type of sensor, units may differ.

Minimum Value: Denotes the lowest sensor reading that can be found within the calibration range. In order to calculate the moisture level accurately, this value is used to normalize the sensor results.

Maximum Value: Denotes the highest sensor reading that can be obtained within the calibration range. Additionally, this value helps to normalize the sensor values.

Moisture Level: Indicates the estimated moisture content based on the sensor's measurement. The following formula is used to determine the moisture level:

$$\text{Level of Moisture} = 1 - \frac{\text{SR} - \text{Min Val}}{400}$$

Where SR is Sensor Reading, and Min Val is the lowest amount.

Unmanned Aerial Systems (UAS) and Drone Mapping for Landslide Prevention and Monitoring

Topographical Monitoring

Concept: Drones that have aerial cameras and LiDAR technology are used to create complex maps of land. As shown in Fig. 3 (Topographical Mapping's), unmanned aerial vehicles (UAVs) equipped with photogrammetric cameras and LiDAR (Light Detection and Ranging) sensors are used to generate detailed topographical information of landslide-prone areas. High-resolution three-dimensional models of the landscape are included in these maps which help identify areas at risk of landslides.

Technologies Employed

LiDAR: Use pulses of laser light to measure distances to the surface of the earth creating complex 3D dimensional maps [8].

Photogrammetric: This technique uses high resolution images taken from different angles to imitate the landscape in 3D.




Figure 3: Topographical Mapping's

Topographical Mapping's Advantages

Benefit	Description
High Resolution	Provides detailed maps with high accuracy.
3D Terrain Models	Helps in visualizing and analyzing the slope and terrain features.
Early Risk Identification	Identifies potential landslide-prone areas based on topographical features.
Data for Planning	Assists in urban planning and infrastructure development in hilly areas.

Analysis of Vegetation

Idea: Drone can investigate how vegetation cover influences soil stability. Vegetation supports the soil by using root systems that prevent flow and hold the soil together [9].

Technologies Employed

Multispectral cameras: Take photographs at different wavelengths, including visible and near-infrared, to assess the density and condition of the plants using multispectral cameras.

Standardized Difference Vegetation Index or NDVI: Standardized Difference Vegetation Index, or NDVI, is a metric of the health and coverage of vegetation calculated from multispectral imagery.

Indicators of Vegetation and Soil Stability

Indicator	Description
High NDVI Value	Indicates healthy, dense vegetation, which stabilizes the soil.
Low NDVI Value	Indicates poor or sparse vegetation, increasing the risk of soil erosion.
Vegetation Cover	Areas with dense vegetation are less likely to experience landslides.



Vegetation Loss	Areas with significant vegetation loss are at higher risk of landslides.
-----------------	--

Imaging infrared

Concept: Water level and makeup of the soil may be evaluated with the use of infrared imaging. Different kinds of soil and moisture levels can be evaluated because multiple substances produce infrared radiation in different ways.

Technologies Employed

Thermal cameras: Water level and the makeup of the soil may be evaluated with the use of infrared imaging. various types of soil and moisture levels can be identified because various materials produce infrared radiation in different ways.

Infrared sensors: Determine which wavelengths are related to the soil moisture and structure.

Infrared Imaging Indicators

Indicator	Description
Soil Temperature	Higher temperatures can indicate dry soil, while cooler areas may indicate moisture.
Moisture Content	Infrared imaging can reveal areas of high soil moisture content, which are at risk.
Soil Composition	Different soil types emit different infrared signatures, helping in identifying soil properties.

Integrated Method for Monitoring and Preventing Landslides

Concept: Integration of data and on the spot remark the usage of an incorporated method, a thorough photo of landslide risks is produced by using merging information from many sensors and drone pics. This approach makes predictions extra correct and dependable and makes it feasible to take preventative movement before landslides occur.

Components

Data Fusion: Records fusion presents an incorporated photograph of landslide-inclined areas by integrating records from many resources, which include drone scans, tiltmeters, geophones, and soil moisture sensors.

Real-Time Monitoring: Actual-time monitoring is the procedure of constantly collecting and studying records to track environmental modifications and appropriately forecast the possibility of landslides [10].

Fusion of Data

Concept: Data fusion combines drone mapping with several sensor kinds to provide a more accurate and complete view of landslide hazard. Its combination allows us to relate to different types of factors like soil moisture, hill movement ground vibration and landscape variations [11].




Figure 4: Method of Data Fusion

Data Sources and Their Contributions

Data Source	Contribution to Risk Assessment
Soil Moisture	Indicates soil saturation levels, crucial for landslide prediction.
Tilt meter	Detects slope movement, providing early warning of instability.
Geophone	Monitors ground vibrations, indicating potential landslide triggers.
Drone Mapping	Offers detailed topographical and vegetation analysis.

Monitoring in Real Time

Idea: Continuous data gathering and processing from sensors and drones is part of real-time monitoring. This enables authorities to correctly predict landslides and quickly identify changes in the surrounding environment [11].




Figure 5: Monitoring System in Real Time

Real-Time Monitoring Benefits

Benefit	Description
Continuous Data Flow	Provides up-to-date information on environmental conditions.
Early Warning System	Generate alerts based on predefined thresholds and patterns.
Predictive Analytics	Uses historical and real-time data to forecast potential landslide events.
Decision Support	Aids authorities in making informed decisions for preventive measures.

It is very nice way to handle the risk of landslides to use data fusion along with real-time monitoring. Authorities can protect people living in risky areas by good predicting and stopping landslides. This is done by combining different types of data, Drone and keeping a close watch on environmental conditions all the time [12].

Key Functions

fuse_data(...): It is Combines different data sources Collect from sensors and drones to assess the overall risk.

send_warning(...): It sends alerts based on risk levels.

real_time_changes_detected(...): Monitors for any changes in the environment and updates risk assessment in real time.

landslide_occurred(): Determines if a landslide happened.

monitor_rehabilitated_area(...): Maintains validity of recovered from landslides area.

take_preventive_action(): If safety is found in hill area proper safety actions are performed.

CONCLUSIONS

The paper talks about techniques that use drone mapping and advanced sensors to monitor and minimize landslides. This method combines different types of sensors like soil moisture sensors, tilt meters, and geophones with drone systems that use LiDAR and photogrammetry, allowing for a more details and analysis of landslide risks [13]. Now, officials are better able to predict landslides by using this careful approach, which allows for more accurate and quicker analysis of hazards, which reduces the harm that landslides cause. It focuses on combining data from different types of sensors and careful to close watch for such hazards early.



It quickly recognizes changes in the environment that might cause a landslide real time monitoring to help avoid the landslide. Drone as well may be used to map the lands surface and analysis ecosystem, which improves the validity of risk evaluation and helps to better resource allocation and control. Our method also speeds up the response and recovery efforts after a disaster. High-resolution drone images are useful for assessing damage and helping in search-and-rescue missions. Continuous monitoring of areas that have been restored ensures their long-term stability. Combining data from various sources leads to better ways to prevent future landslides. Drone mapping and technology for sensors have greatly improved landslide management and control.

Using modern tools and real-time data helps authorities protect people in landslide-prone areas, ensuring their safety and well-being [14]. Future work should aim to improve these technologies and explore other uses that can support existing disaster prevention strategies.

Future Work

- LoRa communication solution for remote areas.
- Using deep reinforcement learning and Artificial Intelligence for autonomous Drone Navigation.
- Extended validation in the field in the west Ghats and Himalayas.

Reference

- [1] Khan, A., Gupta, S., & Gupta, S. K. (2020). Multi-hazard disaster studies: Monitoring, detection, recovery, and management, based on emerging technologies and optimal techniques. *International journal of disaster risk reduction*, 47, 101642.
- [2] Raikes, J., Smith, T. F., Jacobson, C., & Baldwin, C. (2019). Pre-disaster planning and preparedness for floods and droughts: A systematic review. *International Journal of Disaster Risk Reduction*, 38, 101207.
- [3] Deliry, S. I., & Avdan, U. (2021). Accuracy of unmanned aerial systems photogrammetry and structure from motion in surveying and mapping: a review. *Journal of the Indian Society of Remote Sensing*, 49(8), 1997-2017.
- [4] Kashinath, S. A., Mostafa, S. A., Mustapha, A., Mahdin, H., Lim, D., Mahmoud, M. A., ... & Yang, T. J. (2021). Review of data fusion methods for real-time and multi-sensor traffic flow analysis. *IEEE Access*, 9, 51258-51276.
- [5] Hidayat, B., & Egbu, C. O. (2010). A literature review of the role of project management in post-disaster reconstruction.



- [6] Kumar, V., Joshi, A., Thakur, G., Chauhan, N., Kumar, A., & Singh, B. P. (2024). Describing the Research Initiative: Unmanned Aircraft Education in Technology. *Journal of Recent Innovations in Computer Science and Technology*, 1(1), 27-37.
- [7] Lakshmi, V. (2013). Remote sensing of soil moisture. *International Scholarly Research Notices*, 2013(1), 424178.
- [8] Kumar, V., Kumar, L., Kumar, A., Chauhan, N., & Singh, B. P. (2024). Enhancing autonomous navigation and collision avoidance in drone technology using Deep Reinforcement Learning. *International Journal of Technical Research & Science*, 9(04), 24-30.
- [9] Emeka, O. J., Nahazanan, H., Kalantar, B., Khuzaimah, Z., & Sani, O. S. (2021). Evaluation of the effect of hydroseeded vegetation for slope reinforcement. *Land*, 10(10), 995.
- [10] Wang, C., Guo, W., Yang, K., Wang, X., & Meng, Q. (2022). Real-time monitoring system of landslides based on LoRa architecture. *Frontiers in Earth Science*, 10, 899509.
- [11] Khan, A., Gupta, S., & Gupta, S. K. (2020). Multi-hazard disaster studies: Monitoring, detection, recovery, and management, based on emerging technologies and optimal techniques. *International journal of disaster risk reduction*, 47, 101642.
- [12] Kofoed, S., Breen, S., Gough, K., & Aranda, S. (2012). Benefits of remote real-time side-effect monitoring systems for patients receiving cancer treatment. *Oncology reviews*, 6(1).
- [13] Kumar, S., Jain, A., & Pareek, A. (2026). Adaptive Resource-Aware Virtual Machine Placement in Cloud Computing for Optimizing Performance and Cost Efficiency. *Journal of Computers, Mechanical and Management*, 5(3), 228–246. <https://doi.org/10.57159/jcmm.5.3.261068>.
- [14] Dixit, S., Siva Subramanian, S., Srivastava, P., Yunus, A. P., Martha, T. R., & Sen, S. (2024). Numerical-model-derived intensity–duration thresholds for early warning of rainfall-induced debris flows in a Himalayan catchment. *Natural Hazards and Earth System Sciences*, 24(2), 465-480.